

N/A  
**PCT**

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b> <b>H04B 7/185, 7/204</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/49734</b> <b>(43) International Publication Date:</b> 24 August 2000 (24.08.00)
<b>(21) International Application Number:</b> PCT/GB00/00591 <b>(22) International Filing Date:</b> 18 February 2000 (18.02.00)  <b>(30) Priority Data:</b> 99301195.6 18 February 1999 (18.02.99) EP  <b>(71) Applicant (for all designated States except US):</b> ICO SERVICES LIMITED [GB/GB]; 1 Queen Caroline Street, London W6 9BN (GB).  <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> WYRWAS, Richard [GB/GB]; 54 The Mall, Southgate, London N14 6LN (GB).  <b>(74) Agents:</b> MUSKER, David, Charles et al.; R.G.C. Jenkins & Co., 26 Caxton Street, London SW1H 0RJ (GB).		<b>(81) Designated States:</b> JP, US.  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> COMMUNICATIONS APPARATUS AND METHOD  <b>(57) Abstract</b>  A method of mitigating interference in a satellite user uplink signal of a satellite mobile communications system which comprises a plurality of non-geostationary orbiting satellites (4) each radiating a beam pattern of multiple beams, comprising: providing overlapping coverage of a region of the Earth which is subject to interference at an interference frequency, by a first beam of a first satellite (4a) and at least a second beam of a second satellite (4b); determining which of said first or said second beam is more peripheral within their respective satellite beam patterns; and controlling communication (e.g. not using) on the more peripheral said beam to limit reception thereby at said interference frequency.		